

KAMA 2500 PRIME CLEAR OPS SHRINK FILM

CAPABILITIES

- Gauge: .001" to .004" (28 to 101μm)
- Width: 2" to 80" (51 to 2032mm)
- Core size: 3" and 6" standard cores, 8" available
- Roll O.D.: various configurations available
- Custom colors and tints available
- 3 strategic manufacturing locations

PROPERTIES

- Exceptional printability
- Excellent clarity and shrink characteristics
- Great dimensional stability
- Superior yield
- FDA compliant to CFR 21 #177.1640
- Kosher material

TECHNICAL SPECIFICATIONS

	Value	Units	ASTM
Specific Gravity	1.05	grams/cm ²	
Yield	26,360	in ² /lb./mil of thickness	
Tensile Strength at Yield	1,500-4,000	psi	D638
Ultimate Elongation	50 to 125	%	D638
Tensile Modulus	150,000 to 300,000	psi	D790
Typical Range of Use	0 to 175 (-17 to 79)	°F (°C)	

CHEMICAL RESISTANCE

- Acid Resistance.....Good to Excellent
- Strong Oxidizers.....Poor
- AlkaliesExcellent
- Hydrocarbon Solvents.....Poor
- Alcohols.....Good to Excellent
- Fat, Grease, and OilGood

CAPABILITIES AND TECHNICAL SPECIFICATION

The capabilities we list reflect the standard capabilities we offer at the time of this printing. Our capabilities are likely to broaden as we add capacity and expand our product offering. Please call our Sales Team to further discuss your specific needs.

The data herein represents typical values by the methods indicated and should be so considered. Processing variables are a major factor in product performance, this information should serve only as a guide. To the best of our knowledge the data is correct. No warrant is made or implied. The corporation assumes no obligation or liability for the use of data presented.



YOUR TOTAL RESOURCE FOR
EXTRUDED SHEET & FILM

800.628.7598